

2-in-1 Formaldehyde HCHO & TVOC Meter, DT-900A

The HCHO Tester provides a real time measurement of HCHO and TVOC tech product to meet with a variety of occasions air pollution measurement needs, timely responds air pollution. This instrument has a high accuracy, fast response, sensitivity. It is compact, easy to carry, suitable and home, offices, factories, hotels and schools and other indoor environments It can be displayed at any Formaldehyde in the air and the concentration of TVOC, and calculate the value of API (Air Pollution Index).





FEATURES:

- Fuel Cell. HCHO sensor, high accuracy and reliability
- LCD display with backlight
- Real-time display the concentration of HCHO in the air
- Real-time display the concentration of TVOC in the air Real-time display the API
- Two selectable units of measure (ppm, mg/m3)
- Sound and Light alarm when pollution
- Auto power off

TECHNICAL SPECIFICATIONS

HCHO Range 0.00 to 5.00 ppm (or mg/m³)

Resolution 0.01 ppm (or mg/ m³)

Accuracy ±5% F.S.

TVOC 0.00 to 9.99 ppm (or mg/m³) Range

0.01 ppm (or mg/m³) Resolution

Accuracy ±5% F.S.

Response Time ≤ 2s

Operating temperature 0°C to 40°C Storage temperature -10°C to 60°C

Working Voltage 7.4V (Rechargeable battery) Size (H x W x D) 248mm x 160mm x 100mm

Weight 584g

Standard Certification CE, EMC, EN:61326